## 2005 Dodge or Ram Truck RAM 2500 Truck 4WD L6-5.9L DSL Turbo VIN C Vehicle > Maintenance > Service Intervals > Severe Service

## 150000 MILES OR 240000 KILOMETERS

## 150000 miles or 240000 kilometers

Engine Oil

Adjust	Good	Fair	Poor
Band, A/T - 48RE Transmission			
	<b>.</b> .	_ ·	_
Inspect	Good	Fair	Poor
Brake Hose/Line			
Brake Pad			
Brake Shoe			
Constant Velocity Joint			
Inspect the CV joints (if equipped) and front suspension components.			
Cooling System			
Check engine coolant level, hoses, and clamps.			
Exhaust System			
Fan Clutch			
Fluid - A/T			
Fluid - M/T			
Change 6-spd manual transmission (G-56).			
Fluid - Transfer Case			
Check <b>transfer case fluid</b> level.			
Harmonic Balancer - Crankshaft Pulley			
Parking Brake System			
Adjust parking brake if necessary.			
Water Pump			
Inspect water pump weep hole for blockage.			
Lubricate	Good	Fair	Poor
Drive/Propeller Shafts, Bearings and Joints			
Lubricate front drive shaft fitting (2500/3500 4x4).			
Tie Rod End			
Lubricate outer tie rod ends.			
Replace		Rep	laced

Fluid - Differential Change front and rear axle fluid.	
Fluid Filter - A/T - 48RE Transmission	
Fuel Filter	
Oil Filter, Engine	
Rotate	Good Fair Poor
Tires	

(S) = Service Warranty Requirement

(E) = Emission WarrantyRequirement

(B) = Both Service and Emission Warranty Requirement