



RAM 3500 4X2 CREW CAB 60" C/A SRW Trailer Towing Chart - U Market											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight
					Total	Front	Rear	Front	Rear		
6.4L V8 HEMI UPGRADE HD ENGINE	8-SPD AUTO 8HP75-LCV TRANS	4.10	10700	4410	6290	3709	2581	5500	6800	22000	15560
6.4L V8 HEMI UPGRADE HD ENGINE	AUTO TRANS	4.10	10700	4290	6410	3809	2601	5500	6800	25000	18440
6.7L I6 CUMMINS TURBO DIESEL ENGINE	AUTO TRANS	3.42	11600	4250	7350	4556	2793	6000	6800	27500	20000

RAM 3500 4X2 CREW CAB 60" C/A DRW Trailer Towing Chart - U Market											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight
					Total	Front	Rear	Front	Rear		
6.4L V8 HEMI UPGRADE HD ENGINE	8-SPD AUTO 8HP75-LCV TRANS	4.10	13500	6950	6548	3738	2810	5500	9850	22000	15300
6.4L V8 HEMI UPGRADE HD ENGINE	AUTO TRANS	4.10	14000	7270	6734	3898	2836	5500	9850	25000	18110
6.7L I6 CUMMINS TURBO DIESEL ENGINE	AUTO TRANS	3.42	14000	6350	7651	4565	3086	6000	9850	33000	25200



RAM 3500 4X4 CREW CAB 60" C/A SRW Trailer Towing Chart - U Market											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight
					Total	Front	Rear	Front	Rear		
6.4L V8 HEMI UPGRADE HD ENGINE	8-SPD AUTO 8HP75-LCV TRANS	4.10	11000	4290	6709	3981	2728	5500	6800	22000	15140
6.4L V8 HEMI UPGRADE HD ENGINE	AUTO TRANS	4.10	11000	4170	6829	4081	2748	5500	6800	25000	18020
6.7L I6 CUMMINS TURBO DIESEL ENGINE	AUTO TRANS	3.42	12000	4190	7809	4894	2914	6000	6800	27500	19540

RAM 3500 4X4 CREW CAB 60" C/A DRW Trailer Towing Chart - U Market											
Engine	Trans.	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight
					Total	Front	Rear	Front	Rear		
6.4L V8 HEMI UPGRADE HD ENGINE	8-SPD AUTO 8HP75-LCV TRANS	4.10	13500	6450	7045	4014	3031	5500	9850	22000	14800
6.4L V8 HEMI UPGRADE HD ENGINE	AUTO TRANS	4.10	14000	6850	7145	4099	3045	5500	9850	25000	17700
6.7L I6 CUMMINS TURBO DIESEL ENGINE	AUTO TRANS	3.42	14000	5960	8037	4865	3171	6000	9850	33000	24810



NOTES

1. Payload and Max Trailer Weights are ESTIMATED values.
2. All values are shown in pounds unless otherwise stated.
3. Payload and Max Trailer Weight values are rounded to the nearest 10lb.
4. Payload = GVWR – Base Weight
5. Payload and Trailer Weight Rating are mutually exclusive.
6. GAWRs, GVWRs and GCWRs should never be exceeded.
7. Recommended tongue weight determined by class hitch receiver and hardware limits of upfit.
8. Upfit or Aftermarket equipment weight not included in Base Weight.