

2004 Dodge or Ram Truck RAM 3500 Truck 4WD L6-5.9L DSL Turbo VIN 6
Vehicle > Maintenance > Service Intervals

150000 miles or 240000 kilometers

Adjust		Good	Fair	Poor
Band, A/T		☐	☐	☐
Inspect		Good	Fair	Poor
Brake Hose/Line		☐	☐	☐
Brake Pad		☐	☐	☐
Brake Shoe		☐	☐	☐
Constant Velocity Joint	Inspect the CV joints (if equipped) and front suspension components.	☐	☐	☐
Cooling System	Check engine coolant level, hoses, and clamps.	☐	☐	☐
Exhaust System		☐	☐	☐
Fan Clutch		☐	☐	☐
Fluid - M/T		☐	☐	☐
Fluid - Transfer Case	Check transfer case fluid level.	☐	☐	☐
Harmonic Balancer - Crankshaft Pulley		☐	☐	☐
Parking Brake System	Adjust parking brake if necessary.	☐	☐	☐
Water Pump	Inspect water pump weep hole for blockage.	☐	☐	☐
Wheel Bearing	Inspect front wheel bearings. Clean and repack, if necessary.	☐	☐	☐
Replace		Replaced		
Engine Oil				☐
Fluid - A/T				☐
Fluid - Differential	Change front and rear axle fluid.			☐
Fluid Filter - A/T				☐
Fuel Filter				☐
Oil Filter, Engine				☐
Lubricate		Good	Fair	Poor
Tie Rod End	Lubricate outer tie rod ends.	☐	☐	☐
Rotate		Good	Fair	Poor
Tires		☐	☐	☐

(S) = Service Warranty Requirement
(E) = Emission Warranty Requirement
(SE) = Both Service and Emission Warranty Requirement

Please refer to maintenance schedule for a specific mileage interval, for complete information.