

LOAD / INFLATION TABLES

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 15"

7.50R15 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		125 860	
lbs.	S	6300	6600	6900	7200	7500	7800	8100	8400	8700	9000	9300	9610	lbs.	S	4805	
	D	11840	12440	13040	13640	14240	14840	15400	15960	16250	14120	17680	18160		D	4540	
kg.	S	2858	2994	3130	3266	3402	3538	3674	3810	3946	4082	4218	4360	kg.	S	2180	
	D	5371	5643	5915	6187	6459	6731	6985	7239	7371	6405	8020	8240		D	2060	

8.25R15 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		125 860	
lbs.	S		7980	8400	8820	9230	9640	10050	10450	10840	11240	11620	12010	lbs.	S	6005	
	D		15080	15880	16680	17460	18220	18980	19740	20500	21240	21980	22700		D	5675	
kg.	S		3640	3820	4040	4200	4400	4560	4720	4940	5100	5300	5460	kg.	S	2725	
	D		6880	7200	7600	7920	8320	8640	8920	9320	9640	10000	10300		D	2575	

10.00R15 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		125 860	
lbs.	S	9000	9440	9880	10320	10760	11200	11660	12100	12540	13000	13440	13890	lbs.	S	6945	
	D	17080	17920	18760	19600	20440	21280	22160	23000	23840	24720	25520	25580		D	6395	
kg.	S	4082	4282	4482	4681	4881	5080	5289	5489	5688	5897	6096	6300	kg.	S	3150	
	D	7747	8129	8510	8891	9272	9653	10052	10433	10814	11213	11576	11600		D	2900	

10.00R15 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		125 860	
lbs.	S		9220	9710	10200	10670	11140	11610	12070	12530	12980	13440	13880	lbs.	S	6940	
	D		17000	17900	18780	19660	20540	21400	22240	23100	23920	24760	25580		D	6395	
kg.	S		4220	4400	4660	4840	5100	5280	5460	5700	5880	6120	6300	kg.	S	3150	
	D		7760	8120	8600	8920	9400	9720	10080	10520	10840	11280	11600		D	2900	

WHEEL DIAMETER - 16"

7.50R16 LRD

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa		65 450	
lbs.	S	3240	3550	3860	4080	4350	4620	4940						lbs.	S	2470	
	D	5720	6240	6760	7280	7720	8160	8600							D	2150	
kg.	S	1470	1610	1750	1850	1975	2100	2240						kg.	S	1120	
	D	2600	2830	3060	3300	3500	3700	3900							D	975	

7.50R16 LRE

LOAD PER AXLE													LOAD PER TIRE*				
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa		80 550	
lbs.	S	3240	3550	3860	4080	4350	4620	4940	5120	5340	5510			lbs.	S	2755	
	D	5720	6240	6760	7280	7720	8160	8600	8980	9380	9880				D	2470	
kg.	S	1470	1610	1750	1850	1975	2100	2240	2320	2420	2500			kg.	S	1250	
	D	2600	2830	3060	3300	3500	3700	3900	4080	4260	4480				D	1120	



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 16"

7.50R16 LRF

LOAD PER AXLE														LOAD PER TIRE*			
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa		90 620	
lbs.	S	2910	3235	3540	3910	4220	4520	4850	5125	5440	5730	6000	6280	lbs.	S	3140	
	D	5621	6215	6830	7370	8000	8600	9260	9810	10435	11025	11575	12120		D	3030	
kg.	S	1320	1467	1610	1770	1910	2050	2200	2320	2470	2600	2720	2850	kg.	S	1425	
	D	2550	2819	3100	3340	3630	3900	4200	4450	4730	5000	5250	5500		D	1375	

7.50R16 LRF

LOAD PER AXLE														LOAD PER TIRE*			
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		95 660	
lbs.	S	4880	5180	5470	5760	6050	6330	6610						lbs.	S	3305	
	D	9100	9660	10220	10760	11280	11820	12340							D	3085	
kg.	S	2200	2320	2480	2600	2740	2860	3000						kg.	S	1500	
	D	4120	4360	4640	4840	5120	5320	5600							D	1400	

7.50R16 LRG

LOAD PER AXLE														LOAD PER TIRE*		
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa	100 690	
lbs.	S	4680	4970	5250	5530	5800	6080	6340	6610					lbs.	S	3305
	D	9060	9600	10160	10700	11220	11740	12260	12780						D	3195
kg.	S	2140	2240	2400	2500	2640	2760	2900	3000					kg.	S	1500
	D	4120	4320	4640	4840	5120	5320	5600	5800						D	1450

9.00R16 LRD

LOAD PER AXLE														LOAD PER TIRE*		
psi kPa		45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	psi kPa	80 550	
lbs.	S	4850	5292	5732	6172	6400	7054	7500	7940					lbs.	S	3970
	D														D	
kg.	S	2200	2400	2600	2800	2903	3200	3402	3600					kg.	S	1800
	D														D	

11.00R16 LRE

LOAD PER AXLE														LOAD PER TIRE*		
psi kPa		40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	95 660	psi kPa	80 550	
lbs.	S	4756	5261	5766	6234	6702	7164	7692	8138	9040				lbs.	S	4520
	D														D	
kg.	S	2157	2386	2615	2828	3040	3250	3489	3691	4101				kg.	S	2050
	D														D	

11.00R16 LRE

LOAD PER AXLE														LOAD PER TIRE*		
psi kPa		40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	95 660	psi kPa	80 550	
lbs.	S	5520	6060	6600	7120	7630	8140	8640	9130	9610				lbs.	S	4805
	D														D	
kg.	S	2540	2760	2960	3240	3440	3720	3920	4160	4360				kg.	S	2180
	D														D	

LT215/85R16 LRD

LOAD PER AXLE														LOAD PER TIRE*		
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa	65 450	
lbs.	S	3060	3270	3480	3880	4065	4250	4670						lbs.	S	2335
	D	5560	5950	6340	7060	7360	7660	8600							D	2150
kg.	S	1390	1485	1580	1760	1845	1930	2120						kg.	S	1060
	D	2520	2700	2880	3200	3340	3480	3900							D	975

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 16"

LT215/85R16 LRE

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa	80 550	
lbs.	S	3060	3270	3480	3880	4065	4250	4670	4850	5110	5360			lbs.	S	2680
	D	5560	5950	6340	7060	7360	7660	8600	8820	9300	9880				D	2470
kg.	S	1390	1485	1580	1760	1845	1930	2120	2200	2320	2430			kg.	S	1215
	D	2520	2700	2880	3200	3340	3480	3900	4000	4220	4480				D	1120

LT235/85R16 LRD

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa	65 450	
lbs.	S	3480	3725	3970	4410	4630	4850	5246						lbs.	S	2623
	D	6340	6780	7220	8024	8422	8820	9524							D	2381
kg.	S	1580	1690	1800	2000	2100	2200	2380						kg.	S	1190
	D	2880	3080	3280	3640	3820	4000	4320							D	1080

LT235/85R16 LRE

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa		80 550	
lbs.	S	3480	3725	3970	4410	4630	4850	5246	5510	5820	6084			lbs.	S	3042	
	D	6340	6780	7220	8024	8422	8820	9524	10028	10592	11112				D	2778	
kg.	S	1580	1690	1800	2000	2100	2200	2380	2500	2640	2760			kg.	S	1380	
	D	2880	3080	3280	3640	3820	4000	4320	4540	4800	5040				D	1260	

LT225/75R16 LRC

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa	50 350	
lbs.	S	3090	3295	3500	3880									lbs.	S	1940
	D	5600	6000	6400	7060										D	1765
kg.	S	1400	1495	1590	1760									kg.	S	880
	D	2540	2720	2900	3200										D	800

LT225/75R16 LRD

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa	65 450	
lbs.	S	3090	3295	3500	3880	4080	4280	4670						lbs.	S	2335
	D	5600	6000	6400	7060	7430	7800	8600							D	2150
kg.	S	1400	1495	1590	1760	1850	1940	2120						kg.	S	1060
	D	2540	2720	2900	3200	3370	3540	3900							D	975

LT225/75R16 LRE

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa		80 550	
lbs.	S	3090	3295	3500	3880	4080	4280	4670	4870	5140	5360			lbs.	S	2680	
	D	5600	6000	6400	7060	7430	7800	8600	8860	9340	9880				D	2470	
kg.	S	1400	1495	1590	1760	1850	1940	2120	2210	2330	2430			kg.	S	1215	
	D	2540	2720	2900	3200	3370	3540	3900	4020	4240	4480				D	1120	

LT245/75R16 LRE

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa		80 550
lbs.	S	3480	3725	3970	4410	4630	4850	5246	5510	5820	6084			lbs.	S	3042
	D	6340	6780	7220	8024	8422	8820	9524	10028	10592	11112				D	2778
kg.	S	1580	1690	1800	2000	2100	2200	2380	2500	2640	2760			kg.	S	1380
	D	2880	3080	3280	3640	3820	4000	4320	4540	4800	5040				D	1260



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 16"

325/85R16 LRD

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa		65 450	
lbs.	S	6175	6835	7500	8160	8820	9480	10140						lbs.	S	5070	
	D														D		
kg.	S	2801	3100	3402	3701	4001	4300	4600						kg.	S	2300	
	D														D		

325/85R16 LRD

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		35 250	40 280	45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	psi kPa	70 480	
lbs.	S	5820	6480	7120	7750	8360	8960	9560	10140					lbs.	S	5070
	D														D	
kg.	S	2640	2980	3240	3500	3820	4060	4360	4600					kg.	S	2300
	D														D	

WHEEL DIAMETER - 16.5"

8.00R16.5 LRE

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	psi kPa	75 520	
lbs.	S	3300	3570	3830	4100	4360	2660							lbs.	S	2330
	D	6430	6870	7310	7750	8280	8840								D	2210
kg.	S	1500	1620	1740	1860	1980	2110							kg.	S	1055
	D	2920	3120	3320	3520	3760	4000								D	1000

8.75R16.5 LRE

LOAD PER AXLE													MAX LOAD PER TIRE*		
psi kPa		30 210	35 240	40 280	45 310	50 340	55 380	60 410	65 450	70 480	75 520		psi kPa	75 520	
lbs.	S	2580	2910	3240	3560	3880	4180	4480	4780	5070	5360		lbs.	S	2680
	D	4900	5540	6160	6780	7380	7960	8540	9100	9660	10200			D	2550
kg.	S	1180	1300	1480	1600	1720	1880	2000	2160	2260	2420		kg.	S	1210
	D	2240	2480	2840	3080	3320	3600	3840	4120	4360	4640			D	1160

9.50R16.5 LRE

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		45 310	50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	psi kPa	80 550	
lbs.	S	3750	4105	4475	4835	5245	5560	5950	6340					lbs.	S	3170
	D	7145	7825	8520	9205	9995	10560	11300	12040						D	3010
kg.	S	1700	1860	2030	2190	2380	2520	2700	2880					kg.	S	1440
	D	3240	3550	3860	4180	4530	4790	5130	5460						D	1365

WHEEL DIAMETER - 17"

7.50R17 LRD

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		50 350	55 380	60 420	65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	psi kPa	75 520	
lbs.	S	4010	4270	4540	4800	5150	5510							lbs.	S	2755
	D	7490	8110	8634	9160	9690	10400								D	2600
kg.	S	1820	1940	2060	2180	2340	2500							kg.	S	1250
	D	3400	3680	3920	4160	4400	4720								D	1180

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 17.5"

8R17.5 LRD

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		50 350	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	psi kPa		70 480	
lbs.	S	3880	4140	4490	4800	5080								lbs.	S	2540	
	D	7490	8110	8720	9340	9800									D	2450	
kg.	S	1760	1880	2040	2180	2300								kg.	S	1150	
	D	3400	3680	3960	4240	4480									D	1120	

8.5R17.5 LRE

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	90 620	
lbs.	S	5165	5485	5790	6060	6280								lbs.	S	3140
	D	10010	10620	11220	11710	12120									D	3030
kg.	S	2343	2488	2626	2749	2900								kg.	S	1450
	D	4541	4817	5089	5312	5600									D	1400

9R17.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		110 760	
lbs.	S	6080	6420	6770	7110	7455	7795	8140	8480	8820				lbs.	S	4410	
	D	10815	11450	12080	12715	13345	13980	14610	15245	15880					D	3970	
kg.	S	2760	2912	3071	3225	3382	3536	3692	3847	4000				kg.	S	2000	
	D	4905	5194	5479	5768	6053	6341	6627	6915	7200					D	1800	

9.5R17.5 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		125 860
lbs.	S	7980	8400	8820	9230	9640	10050	10450	10840	11240	11620	12010		lbs.	S	6005
	D	15080	15880	16680	17460	18220	18980	19740	20500	21240	21980	22700			D	5675
kg.	S	3640	3820	4040	4200	4400	4560	4720	4940	5100	5300	5450		kg.	S	2725
	D	6880	7200	7600	7920	8320	8640	8920	9320	9640	10000	10300			D	2575

10R17.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	110 760		
lbs.	S	6440	6805	7170	7530	7895	8260	8620	8985	9350				lbs.	S	4675	
	D	12150	12840	13525	14210	14895	15585	16270	16955	17640					D	4410	
kg.	S	2920	3087	3252	3416	3581	3747	3910	4076	4240				kg.	S	2120	
	D	5510	5824	6135	6446	6756	7069	7380	7691	8000					D	2000	

215/75R17.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	95 660	
lbs.	S	5695	6030	6395	6700	7054	7500							lbs.	S	3750
	D	11035	11685	12330	12980	13668	14100								D	3525
kg.	S	2583	2735	2901	3039	3200	3400							kg.	S	1700
	D	5005	5300	5593	5888	6200	6400								D	1600



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 17.5"

215/75R17.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		125 860	
lbs.	S	6120	6440	6750	7080	7390	7720	8020	8360	8660	8990	9300	9610	lbs.	S	4805	
	D	11610	12210	2790	13400	14000	14590	15190	15780	16380	16980	17570	18160		D	4540	
kg.	S	2777	2921	3062	3211	3352	3502	3638	3792	3928	4078	4218	4360	kg.	S	2180	
	D	5265	5536	5802	6078	6350	6618	6890	7158	7430	7702	7970	8240		D	2060	

235/75R17.5 LRF

LOAD PER AXLE													MAX LOAD PER TIRE*				
		psi kPa	65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		105 720
lbs.	S	6010	6380	6740	7100	7450	7800	8140	8480	8820					lbs.	S	4410
	D	11420	12120	12800	13480	14160	14820	15480	16120	16760						D	4190
kg.	S	2740	2900	3080	3220	3420	3540	3740	3860	4000					kg.	S	2000
	D	5200	5480	5840	6120	6480	6760	7080	7360	7600						D	1900

235/75R17.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa		125 860	
lbs.	S	8220	8660	9090	9500	9950	10420	10890	11320	11730	12010			lbs.	S	6005	
	D	15420	16240	17100	17940	18800	19620	20450	21320	22140	22700				D	5675	
kg.	S	3730	3930	4125	4310	4515	4730	4940	5135	5320	5450			kg.	S	2725	
	D	6995	7365	7760	8140	8530	8900	9275	9670	10045	10300				D	2575	

245/70R17.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		115 790	
lbs.	S	6640	7020	7390	7760	8120	8480	8830	9190	9530	9880			lbs.	S	4940	
	D	12580	13280	13980	14680	15380	16040	16720	17380	18040	18700				D	4675	
kg.	S	3000	3200	3360	3540	3700	3880	4020	4160	4340	4480			kg.	S	2240	
	D	5680	6080	6360	6720	7000	7360	7600	7880	8240	8480				D	2120	

245/70R17.5 LRG

LOAD PER AXLE													MAX LOAD PER TIRE*			
	psi kPa	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	120 830	
lbs.	S	6420	6780	7140	7500	7850	8200	8540	8880	9220	9550	9880		lbs.	S	4940
	D	12140	12840	13520	14200	14860	15520	16160	16800	17400	18080	18700			D	4675
kg.	S	2900	3080	3220	3400	3540	3720	3860	4000	4180	4300	4480		kg.	S	2240
	D	5480	5840	6120	6440	6720	7040	7320	7560	7920	8160	8480			D	2120

245/70R17.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa		125 860	
lbs.	S	8400	8820	9230	9640	10050	10450	10840	11240	11620	12010			lbs.	S	6005	
	D	15880	16680	17460	18220	18980	19740	20500	21240	21980	22700				D	5675	
kg.	S	3820	4040	4200	4400	4560	4720	4940	5100	5300	5450			kg.	S	2725	
	D	7200	7600	7920	8320	8640	8920	9320	9640	10111	10300				D	2575	

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 19.5"

8R19.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	90 620	
lbs.	S	5600	5950	6340	6650	7000								lbs.	S	3500
	D	10800	11475	12200	12825	13500									D	3375
kg.	S	2540	2700	2880	3015	3175								kg.	S	1587
	D	4900	5205	5535	5820	6125									D	1531

8R19.5 LRF

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		110 760
lbs.	S	5080	5360	5670	5910	6150	6390	6610	6830	7050				lbs.	S	3525
	D	9840	10280	10720	11140	11560	12000	12400	12800	13220					D	3305
kg.	S	2300	2440	2570	2680	2800	2900	3000	3100	3200				kg.	S	1600
	D	4480	4680	4860	5040	5240	5440	5640	5840	6000					D	1500

225/70R19.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE *		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	85 590	
lbs.	S	6390	6630	6900	7280									lbs.	S	3640
	D	12000	12760	12990	13660										D	3415
kg.	S	2400	3010	3130	3300									kg.	S	1650
	D	5445	5650	5890	6200										D	1550

225/70R19.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE *			
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		95 660	
lbs.	S	5510	5790	6080	6390	6630	6900	7280						lbs.	S	3640	
	D	10400	10880	11440	12000	12460	12980	13660							D	3415	
kg.	S	2500	2620	2760	2900	3000	3140	3300						kg.	S	1650	
	D	4720	4920	5200	5440	5640	5880	6200							D	1550	

225/70R19.5 LRG

LOAD PER AXLE													MAX LOAD PER TIRE*					
		psi kPa	65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		110 760	
lbs.	S	5510	5790	6080	6390	6630	6900	7280	7430	7690	7940				lbs.	S	3970	
	D	10400	10880	11440	12000	12460	12980	13660	13960	14460	15000					D	3750	
kg.	S	2500	2620	2760	2900	3000	3140	3300	3380	3480	3600				kg.	S	1800	
	D	4720	4920	5200	5440	5640	5880	6200	6320	6560	6800					D	1700	

245/70R19.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		90 620	
lbs.	S	7080	7280	7480	7780	8160								lbs.	S	4080	
	D	13260	13660	14060	14620	15440									D	3860	
kg.	S	3210	3300	3395	3530	3700								kg.	S	1850	
	D	6015	6195	6380	6635	7005									D	1750	

245/70R19.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*				
		psi kPa	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		95 660	
lbs.	S	6880	7080	7280	7480	7780	8160								lbs.	S	4080	
	D	12860	13260	13660	14060	14620	15440									D	3860	
kg.	S	3120	3210	3300	3395	3530	3700								kg.	S	1850	
	D	5835	6015	6195	6380	6635	7000									D	1750	



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 19.5"

245/70R19.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa	95 660	
lbs.	S	7280	7480	7780	8160									lbs.	S	4080
	D	13660	14060	14620	15440										D	3860
kg.	S	3300	3400	3540	3700									kg.	S	1850
	D	6200	6360	6640	7000										D	1750

245/70R19.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	110 760	
lbs.	S	6500	6010	7320	7730	8160	8440	8830	9220	9880				lbs.	S	4940
	D	12640	13360	14080	14800	15440	16000	16800	17500	18700					D	4675
kg.	S	2950	2730	3320	3505	3700	3830	4005	4180	4480				kg.	S	2240
	D	5735	6060	6390	6715	7005	7260	7620	7940	8480					D	2120

245/70R19.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		110 760
lbs.	S	7080	7280	7480	7780	8160	8440	8830	9220	9610				lbs.	S	4805
	D	13260	13660	14060	14620	15440	17000	16800	17500	18160					D	4540
kg.	S	3210	3305	3395	3530	3700	3830	4005	4185	4360				kg.	S	2180
	D	6015	6195	6380	6635	7005	7710	7620	7940	8240					D	2060

245/70R19.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa	110 760	
lbs.	S	7280	7480	7780	8160	8380	8670	9080						lbs.	S	4540
	D	13660	14060	14620	15440	15760	16300	17200							D	4300
kg.	S	3300	3400	3540	3700	3800	3940	4120						kg.	S	2060
	D	6200	6360	6640	7000	7160	7400	7800							D	1950

245/70R19.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		120 830
lbs.	S	6780	7140	7500	7850	8200	8540	8880	9220	9550	9880			lbs.	S	4940
	D	12840	13520	14200	14860	15520	16160	16800	17440	18080	18700				D	4675
kg.	S	3080	3220	3400	3540	3720	3860	4000	4180	4300	4480			kg.	S	2240
	D	5840	6120	6440	6720	7040	7320	7560	7920	8160	8480				D	2120

265/70R19.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		110 760	
lbs.	S	7140	7590	8040	8480	8930	9380	9820	10270	10710				lbs.	S	5355	
	D	13600	14440	15280	16120	16940	17780	18620	19440	20280					D	5070	
kg.	S	3239	3443	3647	3847	4051	4255	4454	4658	4860				kg.	S	2430	
	D	6169	6550	6931	7312	7684	8065	8446	8818	9200					D	2300	

265/70R19.5 LRG

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		110 760	
lbs.	S	7230	7680	8110	8540	8970	9390	9800	10210	10620	11020			lbs.	S	5510	
	D	13660	14500	15320	16140	16940	17740	18520	19300	20060	20820				D	5205	
kg.	S	3280	3460	3700	3860	4080	4240	4460	4620	4780	5000			kg.	S	2500	
	D	6200	6520	6960	7280	7720	8040	8440	8720	9040	9440				D	2360	



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 19.5"

265/70R19.5 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE *			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		125 860	
lbs.	S	7360	7800	8220	8660	9090	9500	9950	10420	10890	11320	11730	12020	lbs.	S	6060	
	D	13790	14620	15410	16240	17100	17930	18790	19620	20450	21310	22140	22720		D	5680	
kg.	S	3341	3537	3729	3928	4123	4309	4513	4727	4940	5135	5321	5450	kg.	S	2725	
	D	6258	6633	6990	7366	7757	8133	8523	8900	9276	9666	10043	10300		D	2575	

265/70R19.5 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa		125 860	
lbs.	S	8400	8820	9230	9640	10050	10450	10840	11240	11620	12010			lbs.	S	6005	
	D	15880	16680	17460	18220	18980	19740	20500	21240	21980	22700				D	5675	
kg.	S	3820	4040	4200	4400	4560	4720	4940	5100	5300	5450			kg.	S	2725	
	D	7200	7600	7920	8320	8640	8920	9320	9640	10000	10300				D	2575	

285/70R19.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE *		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		115 790
lbs.	S	7870	8350	8850	9330	9820	10310	11022	11465	11925	12350			lbs.	S	6175
	D	14480	15370	16280	17160	18070	18970	20235	20865	21500	22700				D	5675
kg.	S	3570	3788	4014	4232	4454	4677	5000	5201	5409	5600			kg.	S	2800
	D	6568	6972	7385	7784	8197	8605	9179	9464	9752	10300				D	2575

285/70R19.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	120 830	
lbs.	S	8310	8780	9250	9710	10160	10610	11050	11490	11930	12360	12790		lbs.	S	6395
	D	15600	16500	17360	18220	19080	19920	20760	21580	22400	23220	24020			D	6005
kg.	S	3740	3980	4180	4420	4600	4820	5000	5180	5400	5580	5800		kg.	S	2900
	D	7040	7480	7840	8280	8640	9080	9400	9720	10160	10480	10900			D	2725

285/70R19.5 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE*				
		psi kPa	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		125 860	
lbs.	S	8510	9010	9510	9980	10460	10970	11530	12020	12480	12990	13530	13890	lbs.	S	6945		
	D	15550	16480	17360	18300	19260	20200	21160	22100	23040	24000	24940	25560		D	6390		
kg.	S	3859	4085	4314	4527	4745	4976	5230	5452	5661	5892	6137	6301	kg.	S	3150		
	D	7051	7473	7874	8301	8736	9163	9598	10025	10451	10886	11313	11594		D	2898		

305/70R19.5 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE *				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		115 790	
lbs.	S	8775	9315	9855	10360	10880	11410	11930	12445	12940	13560			lbs.	S	6780	
	D	16430	17415	18400	19360	20315	21310	22330	23370	24340	25580				D	6395	
kg.	S	3980	4225	4470	4699	4935	5176	5411	5645	5870	6150			kg.	S	3075	
	D	7453	7899	8346	8782	9215	9666	10129	10601	11041	11600				D	2900	

445/65R19.5 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		110 760	
lbs.	S	13570	14480	15290	16140	17020	17860	18740	19680	20500				lbs.	S	10250	
	D														D		
kg.	S	5904	6568	6936	7321	7720	8101	8500	8927	9300				kg.	S	4650	
	D														D		



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 20"

8.25R20 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		95 660	
lbs.	S	6700	7110	7520	7910	8310	8700	9080						lbs.	S	4540	
	D	12700	13480	14240	15000	15740	16480	17200							D	4300	
kg.	S	3040	3200	3400	3560	3760	3920	4120						kg.	S	2060	
	D	5760	6040	6440	6760	7120	7400	7800							D	1950	

9.00R20 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		95 660	
lbs.	S	8510	8980	9450	9925	10300								lbs.	S	5150	
	D	15655	16525	17395	18265	18960									D	4740	
kg.	S	3860	4073	4287	4502	4670								kg.	S	2335	
	D	7101	7496	7890	8285	8600									D	2150	

9.00R20 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		100 690	
lbs.	S	8160	8560	8960	9350	9700	10050	10410						lbs.	S	5205	
	D	15440	16180	16920	17640	18340	19040	19760							D	4940	
kg.	S	3700	3880	4060	4240	4400	4560	4720						kg.	S	2360	
	D	7000	7320	7640	8000	8320	8640	8960							D	2240	

9.00R20 LRG

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		105 720	
lbs.	S	7740	8210	8680	9140	9590	10040	10490	10930	11360				lbs.	S	5680	
	D	13840	14700	15520	16340	17160	17960	18760	19540	20320					D	5080	
kg.	S	3540	3740	3980	4160	4400	4580	4820	4980	5160				kg.	S	2580	
	D	6320	6640	7080	7400	7840	8160	8600	8880	9200					D	2300	

10.00R20 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		100 690	
lbs.	S	9385	9900	10430	10940	11510	12080							lbs.	S	6040	
	D	16895	17820	18770	19690	20720	21760								D	5440	
kg.	S	4257	4491	4731	4962	5221	5479							kg.	S	2739	
	D	7664	8083	8514	8931	9399	9870								D	2467	

10.00R20 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		105 720	
lbs.	S	9060	9540	9980	10440	11020	11460	11900	12350					lbs.	S	6175	
	D	17520	18320	19040	19800	20820	21660	22500	23360						D	5840	
kg.	S	4100	4320	4520	4740	5000	5200	5400	5600					kg.	S	2800	
	D	7960	8320	8640	9000	9440	9840	10240	10600						D	2650	

10.00R20 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		115 790	
lbs.	S	9385	9900	10430	10940	11510	12080	12490	12855	13220				lbs.	S	6610	
	D	16895	17820	18770	19690	20720	21760	22480	23130	23800					D	5950	
kg.	S	4257	4491	4731	4962	5221	5479	5665	5831	5997				kg.	S	2998	
	D	7664	8083	8514	8931	9399	9870	10197	10492	10796					D	2699	

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 20"

10.00R20 LRH

LOAD PER AXLE														MAX LOAD PER TIRE *			
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		100 690	
lbs.	S	9370	9940	10500	11060	11610	12150	12690	13220					lbs.	S	6610	
	D	16860	17900	18900	19900	20900	21880	22840	23800						D	5950	
kg.	S	4260	4480	4780	5000	5300	5500	5780	5996					kg.	S	2998	
	D	7680	8080	8600	9000	9520	9920	10400	10796						D	2699	

10.00R20 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		115 790	
lbs.	S	7610	8070	8530	8980	9430	9870	10310	10740	11170	11590	12010		lbs.	S	6780	
	D	17180	18240	19260	20280	21300	22300	23280	24260	25220	26180	27120			D	6005	
kg.	S	3480	3660	3900	4080	4320	4480	4720	4900	5060	5280	5450		kg.	S	3075	
	D	7840	8240	8800	9200	9720	10120	10640	11040	11440	11920	12300			D	2725	

10.00R20 LRH

LOAD PER AXLE													MAX LOAD PER TIRE *				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	9060	9540	9980	10440	11020	11460	11900	12350	12640	12930	13220		lbs.	S	6610	
	D	17520	18320	19040	19800	20820	21660	22500	23360	23580	23800	24020			D	6005	
kg.	S	4100	4320	4520	4740	5000	5200	5400	5600	5740	7880	6000		kg.	S	3000	
	D	7960	8320	8640	9000	9440	9840	10240	10600	10720	10840	10900			D	2725	

11.00R20 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa	115 790	
lbs.	S	9320	10230	10830	11574	12100	12677	13228	13814	14400				lbs.	S	7200
	D	16400	17850	18950	20400	21500	22500	23500	24526	25440					D	6360
kg.	S	4228	4640	4912	5250	5489	5750	6000	6266	6532				kg.	S	3266
	D	7439	8097	8596	9253	9752	10206	10660	11125	11540					D	2885

11.00R20 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		115 790	
lbs.	S	9980	10560	11140	11740	12310	12910	13480	14060	14780				lbs.	S	7390	
	D	17860	18960	20030	21130	22190	23220	24220	25220	26440					D	6610	
kg.	S	4527	4790	5053	5325	5584	5856	6115	6378	6700				kg.	S	3350	
	D	8101	8600	9086	9585	10065	10533	10986	11440	12000					D	3000	

11.00R20 LRH

LOAD PER AXLE													MAX LOAD PER TIRE *			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830
lbs.	S	9880	10400	10900	11380	12010	12410	12810	13220	13740	14260	14780		lbs.	S	7390
	D	19120	19960	20760	21560	22700	23140	23580	24020	25060	26100	27120			D	6780
kg.	S	4480	4720	4940	5160	5450	5640	5820	6000	6240	6480	6700		kg.	S	3350
	D	8680	9040	9440	9800	10300	10520	10720	10900	11360	11840	12300			D	3075

12.00R20 LRG

LOAD PER AXLE														MAX LOAD PER TIRE *			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		105 720	
lbs.	S	10655	11205	11938	12493	13228	13778	14330						lbs.	S	7165	
	D	19840	20945	22045	23150	24250	25355	26460							D	6615	
kg.	S	4833	5083	5415	5667	6000	6250	6500						kg.	S	3250	
	D	9000	9501	10000	10501	11000	11501	12000							D	3000	



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 20"

12.00R20 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		120 830	
lbs.	S	10395	11025	11655	12235	12895	13450	14110	14660	15210	16540			lbs.	S	8270	
	D	18515	19260	20725	21740	22900	23865	25020	26000	27020	28640				D	7160	
kg.	S	4715	5001	5287	5550	5849	6101	6400	6650	6899	7503			kg.	S	3750	
	D	8398	8736	9401	9861	10387	10825	11349	11794	12256	13000				D	3250	

12.00R20 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	10750	11360	11960	12550	13140	13720	14300	14860	15420	15980	16540		lbs.	S	8270	
	D	19200	20300	21380	22440	23480	24520	25540	26560	27560	28560	29560			D	7390	
kg.	S	4840	5160	5400	5700	5940	6240	6460	6700	6980	7200	7500		kg.	S	3750	
	D	9880	9200	9640	10200	10600	11160	11560	11960	12480	12880	13400			D	3350	

12.00R20 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		105 720	
lbs.	S	10655	11205	11938	12493	13228	13778	14330						lbs.	S	7165	
	D	19840	20945	22045	23150	24250	25355	26460							D	6615	
kg.	S	4833	5083	5415	5667	6000	6250	6500						kg.	S	3250	
	D	9000	9501	10000	10501	11000	11501	12000							D	3000	

12.00R20 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	11240	11840	12400	12960	13480	14320	14760	15200	15660	16100	16540		lbs.	S	8270	
	D	21760	22720	23640	24560	25440	26440	27160	27880	28640	29560	30440			D	7610	
kg.	S	5098	5380	5620	5880	6120	6500	6700	6900	7100	7300	7500		kg.	S	3750	
	D	9880	10320	10720	11160	11520	12000	12320	12640	13000	13400	13800			D	3450	

12.50R20 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		10 70	15 100	20 140	25 170	30 210	35 240	40 280	45 310	50 340	55 380	60 410	65 450	psi kPa		50 340	
lbs.	S	2430	3360	4230	5050	5850	6620	7360	8090	8800				lbs.	S	4400	
	D														D		
kg.	S	5480	7280	9540	11140	13200	14680	16600	18020	19400				kg.	S	9700	
	D														D		

14.00R20 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		50 340	55 380	60 410	65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	psi kPa	90 620		
lbs.	S	9940	10860	11560	12440	13100	13960	14620	15460	16080				lbs.	S	8040	
	D														D		
kg.	S	4560	4920	5280	5630	5970	6310	6640	6970	7300				kg.	S	3650	
	D														D		

14.00R20 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		100 690	
lbs.	S	14920	15760	16600	17420	18240	19040	19840						lbs.	S	9920	
	D	26760	28280	29760	31240	32720	34160	35600							D	8900	
kg.	S	6740	7180	7500	7940	8260	8680	9000						kg.	S	4500	
	D	12360	13160	13760	14560	15160	15920	16500							D	4125	

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 20"

14.00R20 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE *		
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa	100 690	
lbs.	S	15760	16600	17420	18240	19040	19840							lbs.	S	9920
	D	28880	30400	31920	33440	34880	36360								D	9090
kg.	S	7180	7500	7940	8260	8680	9000							kg.	S	4500
	D	13160	13760	14560	15160	15920	16500								D	4125

14.00R20 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE *			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		100 690	
lbs.	S	8250	8670	9090	9460	9830	10200							lbs.	S	5100	
	D	7530	7900	8270	8640	9010	9370								D	4685	
kg.	S	3740	3930	4125	4290	4460	4625							kg.	S	2312	
	D	3420	3590	3750	3920	4090	4250								D	2125	

14.00R20 (G20) LRM

LOAD PER AXLE														MAX LOAD PER TIRE *			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		110 760	
lbs.	S	15950	16840	17665	18575	19565	20395	21385	22000					lbs.	S	11000	
	D	29950	31289	32310	33895	35550	36930	38580	39600						D	9920	
kg.	S	7235	7635	8013	8426	8875	9251	9700	10000					kg.	S	5000	
	D	13580	14190	14656	15375	16125	16751	17500	18000						D	4500	

14.5R20 LRL

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		80 550	
lbs.	S	12679	14430											lbs.	S	7215	
	D														D		
kg.	S	5751	6525											kg.	S	3262	
	D														D		

14.5R20 LRL

LOAD PER AXLE														MAX LOAD PER TIRE *		
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		80 550
lbs.	S	12140	12880	13600	14330									lbs.	S	7165
	D														D	
kg.	S	5540	5820	6220	6500									kg.	S	3250
	D														D	

14.75/80R20 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE *		
psi kPa		60 410	70 480	80 550	90 620	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa		125 860
lbs.	S	13228	14316	15404	16492	17580	18124	18668	19212	19756	20300			lbs.	S	10150
	D														D	
kg.	S	6000	6494	6987	7481	7974	8221	8468	8715	8961	9208			kg.	S	4511
	D														D	

15.5/80R20 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE *			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		125 860	
lbs.	S	16120	16960	17820	18640	19460	20200	21000	21800	22600	23400	24250		lbs.	S	12125	
	D														D		
kg.	S	7360	7700	8140	8460	8900	9220	9540	9960	10280	10700	11000		kg.	S	5500	
	D														D		



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 20"

16.00R20 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE*			
		psi kPa	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		100 690
lbs.	S	15432	16170	16910	17637	18740	20000								lbs.	S	10000
	D															D	
kg.	S	7000	7335	7670	8000	8500	9072								kg.	S	4536
	D															D	

16.00R20 LRM

LOAD PER AXLE														MAX LOAD PER TIRE*				
		psi kPa	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		110 760	
lbs.	S	21330	22300	23280	24250	25480	26730	28110	29080						lbs.	S	11000	
	D															D		
kg.	S	9675	10115	10560	11000	11558	12125	12751	13000						kg.	S	6500	
	D															D		

16.00R20 LRM

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		110 760
lbs.	S	18780	19920	21000	22200	23200	24400	25400	26600	27600	28600			lbs.	S	14300
	D														D	
kg.	S	8540	9000	9600	10040	10620	11040	11620	12040	12440	13000			kg.	S	6500
	D														D	

335/80R20 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*				
		psi kPa	30 210	35 240	40 280	45 310	50 340	55 380	60 420	65 450	70 480	75 520	80 550	85 590	psi kPa		55 380	
lbs.	S		5935	6615	7295	7980	8660	9340							lbs.	S	4670	
	D															D		
kg.	S		2690	3000	3308	3620	3930	4236							kg.	S	2118	
	D															D		

335/80R20 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*				
		psi kPa	30 210	35 240	40 280	45 310	50 340	55 380	60 420	65 450	70 480	75 520	80 550	85 590	psi kPa		55 380	
lbs.	S		5760	6510	7250	7960	8660	9350							lbs.	S	4675	
	D															D		
kg.	S		2640	2940	3320	3600	3880	4240							kg.	S	2120	
	D															D		

335/80R20 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*				
		psi kPa	30 210	35 240	40 280	45 310	50 340	55 380	60 420	65 450	70 480	75 520	80 550	85 590	psi kPa		62 430	
lbs.	S		6230	7050	7840	8610	9370	10110	10840	11560					lbs.	S	5780	
	D															D		
kg.	S		2860	3180	3600	3900	4200	4580	4880	5250					kg.	S	2625	
	D															D		

365/80R20 LRL

LOAD PER AXLE														MAX LOAD PER TIRE*				
		psi kPa	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		130 900	
lbs.	S	12100	12830	13480	14160	14880	15620	16240	16930	17700	18465	19230	20000	lbs.	S	10000		
	D														D			
kg.	S	5490	5820	6115	6425	6750	7085	7365	7680	8030	8380	8725	9072	kg.	S	4536		
	D														D			

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 20"

365/80R20 LRL

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		65 450	70 480	75 520	80 550	87 592	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		87 592	
lbs.	S	12070	12810	13540	14260	15660								lbs.	S	7830	
	D														D		
kg.	S	5500	5780	6160	6460	7100								kg.	S	3550	
	D														D		

365/85R20 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		125 860	
lbs.	S	13500	14200	14920	15600	16300	16980	17660	18320	19000	19640	20300		lbs.	S	10150	
	D														D		
kg.	S	6160	6440	6820	7080	7440	7720	7980	8340	8600	8940	9206		kg.	S	4603	
	D														D		

395/85R20 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		95 660	
lbs.	S	15875	16755	17636	18520	19290								lbs.	S	9645	
	D														D		
kg.	S	7201	7600	8000	8401	8750								kg.	S	4375	
	D														D		

395/85R20 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		100 690	
lbs.	S	14460	15340	16200	17060	17920	18760	19580	20400					lbs.	S	10200	
	D														D		
kg.	S	6580	6920	7380	7720	8160	8500	8920	9250					kg.	S	4625	
	D														D		

395/85R20 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	123 850	130 900	135 930	psi kPa		123 850	
lbs.	S	16695	17600	18626	19313	20000	21452	22600	23500	24250	24700			lbs.	S	12350	
	D														D		
kg.	S	7573	8011	8449	8761	9072	9731	10251	10660	11000	12300			kg.	S	6150	
	D														D		

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 20.5"

24R20.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa	85 590	
lbs.	S	25400	26800	28400	30000	31400								lbs.	S	15700
	D														D	
kg.	S	11440	12040	12840	13420	14200								kg.	S	7100
	D														D	

WHEEL DIAMETER - 21"

24R21 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		35 240	40 280	45 310	50 340	55 380	60 410	65 450	70 480	75 520	80 550	85 590	120 830	psi kPa	85 590	
lbs.	S	15440	17180	18880	20600	22200	23800	25400	26800	28400	30000	31400		lbs.	S	15700
	D														D	
kg.	S	6920	7820	8480	9140	9980	10620	11440	12040	12840	13420	14200		kg.	S	7100
	D														D	

WHEEL DIAMETER - 22"

11.00R22 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*					
		psi kPa	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		115 790	
lbs.	S		10570	11400	12230	12640	13260	13780	14300	14920	15320				lbs.	S	7660	
	D		19000	20520	22020	22760	23880	24800	25740	26860	27600					D	6900	
kg.	S		4795	5171	5548	5734	6015	6251	6486	6768	6950				kg.	S	3475	
	D		8618	9308	9988	10324	10832	11249	11676	12184	12519					D	3130	

11.00R22 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	10480	11040	11580	12080	12790	13300	13820	14320	14760	15200	15660		lbs.	S	7830	
	D	20320	21200	22080	22920	23360	24380	25400	26440	27160	27880	28640			D	7160	
kg.	S	4760	5000	5260	5480	5800	6040	6280	6500	6700	6900	7100		kg.	S	3550	
	D	9200	9600	10000	10400	10600	11080	11560	12000	12320	12640	13000			D	3250	

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.
 * Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.
NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.
 S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 22.5"

9R22.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE *		
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		95 660
lbs.	S	7400	7825	8100	8615	9080								lbs.	S	4540
	D	13895	14685	15340	16200	17200									D	4300
kg.	S	3360	3550	3675	3910	4120								kg.	S	2060
	D	6305	6660	6960	7350	7800									D	1950

9R22.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		105 720	
lbs.	S	6740	7120	7460	7780	8160	8470	8780	9080					lbs.	S	4540	
	D	13080	13640	14200	14760	15440	16020	16600	17200						D	4300	
kg.	S	3060	3220	3380	3520	3700	3840	3980	4120					kg.	S	2060	
	D	5920	6200	6440	6680	7000	7280	7560	7800						D	1950	

10R22.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		95 660	
lbs.	S	8510	8980	9450	9925	10300								lbs.	S	5150	
	D	15655	16525	17395	18265	18960									D	4740	
kg.	S	3860	4075	4290	4500	4672								kg.	S	2336	
	D	7100	7500	7890	8285	8600									D	2150	

10R22.5 LRF

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		100 690	
lbs.	S	8160	8560	8960	9350	9700	10050	10410						lbs.	S	5205	
	D	15440	16180	16920	17640	18340	19040	19760							D	4940	
kg.	S	3700	3880	4060	4240	4400	4560	4720						kg.	S	2360	
	D	7000	7320	7640	8000	8320	8640	8960							D	2240	

10R22.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE *			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		105 720	
lbs.	S	8510	8980	9450	9925	10300	11200	11360						lbs.	S	5680	
	D	15655	16525	17395	18265	18960	19980	20320							D	5080	
kg.	S	3860	4073	4290	4500	4675	5080	5153						kg.	S	2576	
	D	7100	7500	7890	8285	8600	9065	9216							D	2304	

10R22.5 LRG

LOAD PER AXLE													MAX LOAD PER TIRE *			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		115 790
lbs.	S	8160	8560	8960	9350	9700	10050	10410	10720	11030	11350			lbs.	S	5675
	D	15440	16180	16920	17640	18340	19040	19760	20300	20840	21420				D	5355
kg.	S	3700	3880	4060	4240	4400	4560	4720	4860	5000	5150			kg.	S	2575
	D	7000	7320	7640	8000	8320	8640	8960	9200	9440	9720				D	2430

11R22.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE *			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		100 690	
lbs.	S	9385	9900	10430	10940	11510	12350							lbs.	S	6175	
	D	17000	17800	18600	19700	21200	23000								D	5750	
kg.	S	4260	4490	4730	4960	5220	5600							kg.	S	2800	
	D	7710	8075	8440	8940	9620	10400								D	2600	



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 22.5"

11R22.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		105 720	
lbs.	S	9060	9540	9980	10440	11020	11460	11900	12350					lbs.	S	6175	
	D	17520	18320	19040	19800	20820	21660	22500	23360						D	5840	
kg.	S	4100	4320	4520	4740	5000	5200	5400	5600					kg.	S	2800	
	D	7960	8320	8640	9000	9440	9840	10240	10600						D	2650	

11R22.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*				
		psi kPa	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		115 790	
lbs.	S	9385	9900	10430	10940	11510	12350	12600	12855	13220					lbs.	S	6610	
	D	16895	17820	18770	19690	20720	22700	23110	23520	23800						D	5950	
kg.	S	4260	4490	4730	4960	5220	5600	5715	5830	6000					kg.	S	3000	
	D	7665	8085	8515	8930	9400	10300	10485	10670	10800						D	2700	

11R22.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*				
		psi kPa	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	9060	9540	9980	10440	11020	11460	11900	12350	12640	12930	13220		lbs.	S	6610		
	D	17520	18320	19040	19800	20820	21660	22500	23360	23580	23800	24020			D	6005		
kg.	S	4100	4320	4520	4740	5000	5200	5400	5600	5740	5880	6000		kg.	S	3000		
	D	7960	8320	8640	9000	9440	9840	10240	10600	10720	10840	10900			D	2725		

11R22.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	9020	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880		lbs.	S	6940	
	D	16620	17560	18500	19420	20320	21220	22100	22980	23860	24720	25580			D	6395	
kg.	S	4060	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300		kg.	S	3150	
	D	7480	7960	8360	8840	9200	9640	10000	10360	10800	11160	11600			D	2900	

12R22.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*					
		psi kPa	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900			psi kPa	115 790	
lbs.	S	9980	10560	11140	11740	12310	12910	13480	14060	14780					lbs.	S	7390		
	D	17700	18700	19800	20800	22000	23200	24400	25600	27000						D	6750		
kg.	S	4527	4790	5053	5325	5584	5856	6115	6378	6704					kg.	S	3352		
	D	8029	8482	8981	9435	9979	10524	11068	11612	12248						D	3062		

12R22.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*				
		psi kPa	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	9880	10400	10900	11380	12010	12410	12810	13220	13740	14260	14780			lbs.	S	7390	
	D	19120	19960	20760	21560	22700	23140	23580	24020	25060	26100	27120				D	6780	
kg.	S	4480	4720	4940	5160	5450	5640	5820	6000	6240	6480	6700			kg.	S	3350	
	D	8680	9040	9400	9760	10300	10520	10720	10900	11360	11840	12300				D	3075	

12R22.5 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*				
		psi kPa	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	120 830	
lbs.	S	10170	10750	11320	11880	12440	12990	13540	14080	14600	15140	15660		lbs.	S	7830	
	D	18040	19060	20060	21060	22060	23020	24000	24940	25900	26840	27760			D	6940	
kg.	S	4580	4880	5100	5400	5620	5920	6120	6340	6620	6820	7100		kg.	S	3550	
	D	8120	8680	9080	9600	9960	10480	10880	11240	11760	12120	12600			D	3150	

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.
 * Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.
NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.
 S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 22.5"

13R22.5 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*				
		psi kPa	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830
lbs.	S	10750	11360	11960	12550	13140	13720	14300	14860	15420	15980	16540	lbs.		S	8270	
	D	19200	20300	21380	22440	23480	24520	25540	26560	27560	28560	29560			D	7390	
kg.	S	4840	5160	5400	5700	5940	6240	6460	6700	6980	7200	7500	kg.		S	3750	
	D	9880	9200	9640	10200	10600	11160	11560	11960	12480	12880	13400			D	3350	

235/80R22.5 LRG

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa	90 620	
lbs.	S	8070	8555	9085	9350									lbs.	S	4675
	D	15255	16140	17110	17640										D	4410
kg.	S	3660	3880	4120	4240									kg.	S	2120
	D	6920	7320	7760	8000										D	2000

235/80R22.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		100 690	
lbs.	S	7185	7630	8070	8555	9085	9350							lbs.	S	4675	
	D	13580	14375	15255	16140	17110	17640								D	4410	
kg.	S	3200	3460	3660	3880	4120	4240							kg.	S	2120	
	D	6160	6520	6920	7320	7760	8000								D	2000	

235/80R22.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	110 760	
lbs.	S	6940	7290	7720	7950	8280	8600	8910	9220	9350				lbs.	S	4675
	D	12640	13260	14560	14460	15060	15880	16220	16780	17200					D	4300
kg.	S	3140	3300	3500	3600	3760	3900	4040	4180	4240				kg.	S	2120
	D	5720	6000	6600	6560	6840	7200	7360	7600	7800					D	1950

235/80R22.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
		psi kPa	65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		110 760
lbs.	S	6140	6510	6880	7250	7610	7960	8320	8660	9010	9350				lbs.	S	4675
	D	11580	12280	12980	13680	14360	15020	15680	16340	17000	17640					D	4410
kg.	S	2780	2940	3120	3280	3460	3600	3780	3920	4060	4240				kg.	S	2120
	D	5280	5520	5920	6160	6520	6800	7160	7400	7680	8000					D	2000

255/70R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		115 790
lbs.	S	7620	8045	8470	8895	9305	9610	10000	10545	11020				lbs.	S	5510
	D	14085	14850	15620	16385	17120	17680	18160	19405	20280					D	5070
kg.	S	3456	3649	3842	4035	4221	4359	4536	4783	4999				kg.	S	2499
	D	6389	6736	7085	7432	7766	8020	8237	8802	9199					D	2299

255/70R22.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*			
		psi kPa	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa		120 830
lbs.	S	8380	8740	9100	9350	9790	10130	10410	10800	11020					lbs.	S	5510
	D	15880	16440	17100	17640	17820	18440	18700	19660	20280						D	5070
kg.	S	3800	3960	4120	4240	4440	4600	4720	4900	5000					kg.	S	2500
	D	7200	7440	7760	8000	8080	8360	8480	8920	9200						D	2300



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 22.5"

255/80R22.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		95 660	
lbs.	S	8470	8930	9420	9920	10410								lbs.	S	5205	
	D	15640	16540	17420	18300	19240									D	4810	
kg.	S	3840	4050	4275	4500	4725								kg.	S	2362	
	D	7095	7505	7905	8300	8730									D	2182	

255/80R22.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		105 720	
lbs.	S	7500	8000	8470	8930	9420	9920	10410						lbs.	S	5205	
	D	13870	14780	15640	16540	17420	18300	19240							D	4810	
kg.	S	3404	3630	3845	4050	4275	4500	4725						kg.	S	2362	
	D	6294	6705	7095	7505	7905	8300	8730							D	2182	

255/80R22.5 LRG

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		110 760
lbs.	S	7750	8140	8600	8880	9240	9610	9950	10300	10410				lbs.	S	5205
	D	14100	14820	15440	16160	16820	17640	18100	18740	19220					D	4805
kg.	S	3520	3700	3900	4020	4200	4360	4520	4680	4720				kg.	S	2360
	D	6400	6720	7000	7320	7640	8000	8200	8520	8720					D	2180

275/70R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*		
psi kPa		90 620	95 660	100 690	105 720	110 760	115 790	120 830	123 850	131 900	135 930		psi kPa	123 (D) 850	131 (S) 900
lbs.	S	103505	10810	11260	11710	12150	12590	13030	13317	13460	13890		lbs.	S	6945
	D	20320	21220	22100	22980	23860	24720	25290	25580					D	6395
kg.	S	4680	4920	5100	5280	5500	5680	5900	5990	6080	6300		kg.	S	3150
	D	9200	9640	10000	10360	10800	11160	11470	11600					D	2900

275/70R22.5 LRG

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830
lbs.	S	9020	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880		lbs.	S	6940
	D	16620	17560	18500	19420	20320	21220	22100	22980	23860	24720	25580			D	6395
kg.	S	4060	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300		kg.	S	3150
	D	7480	7960	8360	8840	9200	9640	10000	10360	10800	11160	11600			D	2900

275/80R22.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	123 850	130 900	psi kPa		100 690	
lbs.	S	10420	10840	11350	11670	12080	12350							lbs.	S	6175	
	D	18960	19720	20820	21240	21980	22700								D	5675	
kg.	S	4480	4920	5150	5300	5480	5600							kg.	S	2800	
	D	8240	8960	9440	9640	9980	10300								D	2575	

275/80R22.5 LRG

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		110 760
lbs.	S	9000	9450	9880	10310	10740	11020	11560	11960	12350				lbs.	S	6175
	D	16380	17200	18160	18760	19540	20280	21040	21760	22700					D	5675
kg.	S	4080	4280	4480	4680	4880	5000	5240	5420	5600				kg.	S	2800
	D	7440	7800	8240	8520	8880	9200	9560	9880	10300					D	2575

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.
 * Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.
NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.
 S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 22.5"

275/80R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE *			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830
lbs.	S	9030	9540	10050	10550	11040	11530	12010	12490	12970	13440	13900		lbs.	S	6950
	D	16600	17540	18480	19400	20300	21200	22100	22980	23840	24700	25560			D	6390
kg.	S	4060	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300		kg.	S	3150
	D	7480	7960	8360	8840	9200	9640	10000	10360	10800	11160	11600			D	2900

275/80R22.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		115 790	
lbs.	S	9650	10180	10730	11250	11840	12350	12690	13230	13880				lbs.	S	6940	
	D	17400	18350	19330	20280	21340	22700	23115	23530	24700					D	6175	
kg.	S	4380	4620	4870	5105	5370	5605	5760	6000	6296				kg.	S	3148	
	D	7895	8325	8770	9200	9680	10300	10485	10675	11204					D	2801	

275/80R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	9020	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880		lbs.	S	6940	
	D	16620	17560	18500	19420	20320	21220	22100	22980	23860	24720	25580			D	6395	
kg.	S	4060	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300		kg.	S	3150	
	D	7480	7960	8360	8840	9200	9640	10000	10360	10800	11160	11600			D	2900	

275/80R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	9300	9830	10350	10870	11380	11880	12380	12870	13360	13840	14320		lbs.	S	7160	
	D	17180	18160	19120	20060	21000	21940	22860	23760	24660	25560	26440			D	6610	
kg.	S	4200	4480	4680	4940	5140	5420	5600	5800	6060	6240	6500		kg.	S	3250	
	D	7760	8240	8640	9120	9520	10000	10360	10720	11200	11520	12000			D	3000	

285/60R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE *			
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa		130 900
lbs.	S	9410	9880	10340	10800	11250	11700	12140	12580	13020	13460	13880		lbs.	S	6940
	D	17340	18200	19060	19900	20740	21560	22380	23200	24000	24780	25580			D	6395
kg.	S	4240	4500	4680	4920	5100	5280	5500	5680	5900	6080	6300		kg.	S	3150
	D	7840	8280	8600	9040	9360	9720	10120	10440	10880	11200	11600			D	2900

295/80R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		120 830	
lbs.	S	10150	10720	11290	11860	12430	13000	13580	14160	14740	15660			lbs.	S	7830	
	D	17750	18800	19850	20900	21930	23000	24000	25100	26110	27800				D	6950	
kg.	S	4605	4865	5121	5380	5640	5900	6160	6425	6690	7100			kg.	S	3550	
	D	8050	8530	9005	9480	9950	10435	10890	11385	11845	12610				D	3152	

295/80R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		115 790
lbs.	S	9940	10500	11060	11610	12150	12690	13220	13740	14260	14780			lbs.	S	7390
	D	18240	19260	20280	21300	22300	23280	24260	25220	26180	27120				D	6780
kg.	S	4500	4800	5020	5300	5520	5800	6020	6220	6500	6700			kg.	S	3350
	D	8240	8800	9200	9720	10120	10640	11040	11440	11920	12300				D	3075



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 22.5"

295/80R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	120 830	
lbs.	S	10170	10750	11320	11880	12440	12990	13540	14080	14600	15140	15660		lbs.	S	7830
	D	18040	19060	20060	21060	22060	23020	24000	24940	25900	26840	27760			D	6940
kg.	S	4580	4880	5100	5400	5620	5920	6120	6340	6620	6820	7100		kg.	S	3550
	D	8120	8680	9080	9600	9960	10480	10880	11240	11760	12120	12600			D	3150

305/70R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	123 850	130 900	psi kPa	115 (D) 790	123 (S) 850
lbs.	S	9368	9920	10500	11000	11500	12000	12700	13200	13800	14380	14780		lbs.	S	7390
	D	17880	19000	20000	21100	22100	23200	24200	25200	27120					D	6780
kg.	S	4250	4500	4763	4990	5216	5443	5761	5998	6260	6486	6704		kg.	S	3352
	D	7611	8618	9072	9571	10070	10534	10977	11431	12302					D	3075

305/70R22.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	120 830	
lbs.	S	9600	10150	10690	11220	11740	12260	12770	13280	13780	14280	14780		lbs.	S	7390
	D	17620	18620	19600	20580	21540	22500	23440	24380	25300	26220	27120			D	6780
kg.	S	4320	4600	4820	5100	5300	5580	5780	5980	6240	6440	6700		kg.	S	3350
	D	7920	8480	8840	9360	9720	10240	10600	10960	11480	11840	12300			D	3075

305/70R22.5 LRL

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	120 830	
lbs.	S	10170	10750	11320	11880	12440	12990	13540	14080	14600	15140	15660		lbs.	S	7830
	D	18040	19060	20060	21060	22060	23020	24000	24940	25900	26840	27760			D	6940
kg.	S	4580	4880	5100	5400	5620	5920	6120	6340	6620	6820	7100		kg.	S	3550
	D	8120	8680	9080	9600	9960	10480	10880	11240	11760	12120	12600			D	3150

315/80R22.5 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	123 850	130 900	psi kPa	120 830	
lbs.	S	11313	11895	12475	13055	13635	14215	14795	15375	15955	16540			lbs.	S	8270
	D	18878	21250	22440	23625	24815	26000	27185	18370	18370	29560				D	7390
kg.	S	5132	5395	5660	5925	6185	6450	6710	6975	7240	7500			kg.	S	3750
	D	8563	9640	10180	10180	11260	11795	12330	12870	12869	13400				D	3352

315/80R22.5 LRL

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa	115 (D) 790	120 (S) 830
lbs.	S		10750	11360	11960	12550	13140	13720	14300	14860	15420	15980	16540	lbs.	S	8270
	D	18720	19880	21000	22120	23220	24300	25380	26440	27480	28520	29560			D	7390
kg.	S		4840	5160	5400	5700	5940	6240	6460	6700	6980	7200	7500	kg.	S	3750
	D	8560	9000	9600	10040	10600	11040	11600	12040	12440	13000	13408			D	3352

315/80R22.5 LRL

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa	130 900	
lbs.	S	11700	12280	12870	13350	13990	14620	15260	15900	16540	16970	17500	18000	lbs.	S	9000
	D	19190	20420	21650	23120	24220	25320	26420	27540	28640	30240	31570	33020		D	8255
kg.	S	5542	5763	5984	6056	6346	6632	6922	7212	7503	7698	7938	8165	kg.	S	4082
	D	9265	9717	10169	10487	10986	11485	11984	12492	12991	13717	14320	14978		D	3744

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.
 * Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.
NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.
 S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 22.5"

315/80R22.5 LRL

LOAD PER AXLE													MAX LOAD PER TIRE *			
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa	130 900	
lbs.	S	12330	12940	13540	14140	14740	15320	15900	16480	17060	17620	18180		lbs.	S	9090
	D	22440	23540	24640	25740	26800	27880	28960	30000	31040	32040	33080			D	8270
kg.	S	5560	5880	6120	6440	6680	6900	7200	7440	7740	7960	8250		kg.	S	4125
	D	10120	10680	11120	11720	12120	12560	13120	13520	14040	14480	15000			D	3750

315/80R22.5 LRL

LOAD PER AXLE													MAX LOAD PER TIRE*		
psi kPa		85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa	130 900	
lbs.	S	14770	15350	15930	16515	17095	17675	18260	18840	19420	20000		lbs.	S	10000
	D	22070	23120	24220	25320	26420	27540	28640	30240	31570	33020			D	8255
kg.	S	6700	6965	7225	7490	7755	8020	8285	8545	8810	9075		kg.	S	4535
	D	10010	10490	10990	11485	11985	12495	12990	13720	14320	14976			D	3744

315/80R22.5 LRL

LOAD PER AXLE													MAX LOAD PER TIRE *				
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa		130 900	
lbs.	S	13560	14240	14900	15560	16220	16860	17500	18140	18760	19380	20000		lbs.	S	10000	
	D	22440	23540	24640	25740	26800	27880	28960	30000	31040	32040	33080			D	8270	
kg.	S	6120	6460	6740	7080	7340	7580	7920	8180	8500	8740	9070		kg.	S	4535	
	D	10120	10680	11120	11720	12120	12560	13120	13520	14040	14480	15000			D	3750	

385/65R22.5 XZY LRJ

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		125 860	
lbs.	S	12665	13280	13880	14560	15160	15780	16440	17060	17800	18000	18740		lbs.	S	9370	
	D														D		
kg.	S	5745	6024	6296	6604	6877	7158	7457	7738	8000	8316	8500		kg.	S	4250	
	D														D		

385/65R22.5 XTE2 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE *			
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa		130 900
lbs.	S	13460	14120	14780	15440	16080	16720	17360	17980	18600	19220	19840		lbs.	S	9920
	D														D	
kg.	S	6060	6420	6680	7020	7280	7520	7860	8100	8440	8680	9000		kg.	S	4500
	D														D	

425/65R22.5 LRL

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	123 850	130 900	psi kPa		125 860	
lbs.	S	15340	16000	16800	17680	18440	19180	20000	21000	21480	22220	22800		lbs.	S	11400	
	D														D		
kg.	S	6958	7250	7620	8020	8364	8700	9072	9526	9743	10079	10342		kg.	S	5171	
	D														D		

425/65R22.5 LRL

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		125 860
lbs.	S	15160	15960	16740	17540	18300	19080	19840	20600	21400	22000	22800		lbs.	S	11400
	D														D	
kg.	S	6880	7200	7620	7920	8340	8640	8940	9340	9620	10020	10300		kg.	S	5150
	D														D	



Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 22.5"

445/50R22.5 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa	100 690	
lbs.	S	12100	12840	13560	14280	15000	15700	16400	17080					lbs.	S	8540
	D														D	
kg.	S	5500	5800	6180	6460	6840	7120	7480	7750					kg.	S	3875
	D														D	

445/50R22.5 LRL

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	13260	14000	14740	15480	16200	16920	17640	18340	19020	19720	20400		lbs.	S	10200	
	D														D		
kg.	S	5960	6360	6660	7040	7320	7700	7980	8260	8620	8900	9250		kg.	S	4625	
	D														D		

445/65R22.5 LRL

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	120 830	
lbs.	S	16460	17320	18180	18960	19740	20400	21200	22000	22800	23400	24600		lbs.	S	12300
	D														D	
kg.	S	7440	7900	8250	8640	8940	9250	9640	9920	10300	10580	11200		kg.	S	5600
	D														D	

445/65R22.5 LRL

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa	130 900	
lbs.	S	17360	18220	19080	19920	20800	21600	22400	23200	24000	24800	25600		lbs.	S	12800
	D														D	
kg.	S	7820	8280	8600	9060	9380	9700	10140	10460	10880	11180	11600		kg.	S	5800
	D														D	

445/45R22.5 LRM

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa		130 900	
lbs.	S	15860	16660	17440	18200	18960	19720	20400	21200	22000	22600	23400		lbs.	S	11700	
	D														D		
kg.	S	7140	7560	7860	8280	8580	8860	9260	9560	9940	10220	10600		kg.	S	5300	
	D														D		

445/55R22.5 LRL

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	psi kPa		125 860	
lbs.	S	14620	15400	16160	16920	17660	18400	19140	19860	20600	21200	22000		lbs.	S	11000	
	D														D		
kg.	S	6680	7000	7400	7700	8100	8380	8680	9060	9340	9720	10000		kg.	S	5000	
	D														D		

495/45R22.5 LRM

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa	130 900	
lbs.	S	17360	18220	19080	19920	20800	21600	22400	23200	24000	24800	25600		lbs.	S	12800
	D														D	
kg.	S	7820	8280	8600	9060	9380	9700	10140	10460	10880	11180	11600		kg.	S	5800
	D														D	

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 24"

11.00R24 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa	110 (D) 760	120 (S) 830
lbs.	S	10800	11310	11720	12280	12840	13360	13880	14380	14860	15340	15800	16260	lbs.	S	8130
	D	20890	21750	22520	23440	24360	25240	26080	26920	27720	28520				D	7130
kg.	S	4900	5128	5316	5570	5824	6060	6296	6523	6740	6958	7167	7376	kg.	S	3688
	D	9476	9865	10215	10632	11050	11449	11830	12211	12574	12937				D	3234

11.00R24 LRH

LOAD PER AXLE													MAX LOAD PER TIRE *			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa	120 830	
lbs.	S	11140	11720	12280	12840	13560	14120	14680	15220	15660	16100	16540		lbs.	S	8270
	D	21560	22520	23440	24360	24700	25720	26760	27760	28640	29520	30440			D	7610
kg.	S	5060	5320	5580	5820	6150	6400	6660	6900	7100	7300	7500		kg.	S	3750
	D	9760	10200	10640	11040	11200	11680	12160	12600	13000	13400	13800			D	3450

12.00R24 LRJ

LOAD PER AXLE														MAX LOAD PER TIRE *		
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa	110 (D) 760	120 (S) 830
lbs.	S	12270	12840	13320	13960	14560	15160	15760	16320	16900	17420	17940	18460	lbs.	S	9230
	D	23690	24670	25560	26600	27640	28640	29640	30560	31480	32400				D	8100
kg.	S	5593	5849	6042	6332	6604	6877	7149	7403	7666	7902	8138	8373	kg.	S	4186
	D	10746	11189	11594	12066	12538	12991	13445	13862	14279	14679				D	3674

12.00R24 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE *			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830
lbs.	S	12660	13320	13960	14560	15160	16100	16620	17140	17640	18200	18740		lbs.	S	9370
	D	24480	25560	26600	27640	28640	29560	30440	31320	32200	33200	34160			D	8540
kg.	S	5740	6040	6340	6600	6880	7300	7540	7780	8000	8260	8500		kg.	S	4250
	D	11120	11440	12080	12560	13000	13400	13800	14200	14600	15040	15500			D	3875

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes.

Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 24.5"

11R24.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		100 690	
lbs.	S	8910	9410	9920	10470	11025	11560	12210	12860					lbs.	S	6430	
	D	15010	15970	16930	18140	19270	20490	21880	24000						D	6000	
kg.	S	4042	4270	4500	4750	5000	5245	5540	5835					kg.	S	2917	
	D	6810	7245	7680	8230	8740	9295	9925	10888						D	2722	

11R24.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		105 720	
lbs.	S	9640	10140	10620	11100	11680	12190	12700	13220					lbs.	S	6610	
	D	18640	19480	20280	21040	22040	22700	23360	24020						D	6005	
kg.	S	4380	4600	4820	5040	5300	5540	5780	6000					kg.	S	3000	
	D	8440	8840	9200	9560	10000	10320	10640	10900						D	2725	

11R24.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		115 790
lbs.	S	8910	9410	9920	10470	11025	11560	12210	12860	13260	13660	14060		lbs.	S	7030
	D	14600	15970	16895	1782	18770	19690	20720	24000	23880	24600	25320			D	6330
kg.	S	4012	4268	4500	4449	5001	5244	5538	5835	6015	6196	6380		kg.	S	3190
	D	6810	7244	7664	8083	8514	8931	9399	10888	10832	11159	11485			D	2871

11R24.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830
lbs.	S	9640	10140	10620	11100	11680	12190	12700	13220	13580	13940	14320		lbs.	S	7160
	D	18640	19480	20280	21040	22040	22700	23360	24020	24820	25620	26440			D	6610
kg.	S	4380	4600	4820	5040	5300	5540	5780	6000	6160	6320	6500		kg.	S	3250
	D	8440	8840	9200	9560	10000	10320	10640	10900	11280	11640	12000			D	3000

12R24.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa	110 (D) 760	120 (S) 830
lbs.	S	10120	10606	11040	11580	12080	12580	13060	13540	14000	14440	14880	15320	lbs.	S	7660
	D	19660	20464	21200	22080	22920	23760	24560	25320	26120	26880				D	6720
kg.	S	4591	4811	5008	5253	5479	5706	5924	6142	6350	6550	6750	6949	kg.	S	3475
	D	8915	9282	9616	10015	10397	10778	11140	11485	11848	12193				D	3048

12R24.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE*			
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830
lbs.	S	10480	11040	11580	12080	12790	13300	13820	14320	14760	15200	15660		lbs.	S	7830
	D	20320	21200	22080	22920	23360	24380	25400	26440	27160	27880	28640			D	7160
kg.	S	4760	5000	5260	5480	5800	6040	6280	6500	6700	6900	7100		kg.	S	3550
	D	9200	9600	10000	10400	10600	11080	11560	12000	12320	12640	13000			D	3250

275/80R24.5 LRG

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		100 690
lbs.	S	9880	10420	10840	11350	11670	12080	12350						lbs.	S	6175
	D	18160	18960	19720	20820	21240	21980	22700							D	5675
kg.	S	4480	4725	4920	5150	5300	5480	5600						kg.	S	2800
	D	8240	8600	8960	9440	9640	9960	10300							D	2575

Load and inflation industry standards are in a constant state of change. Michelin continually updates its product information to reflect these changes. Therefore, printed material may not reflect the current load and inflation information.

* Always refer to the tire sidewall markings for maximum load and pressure information to determine the proper load/inflation table.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

S = Single configuration – 2 tires per axle. D = Dual configuration – 4 tires per axle.

WHEEL DIAMETER - 24.5"

275/80R24.5 LRG

LOAD PER AXLE													MAX LOAD PER TIRE*				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		110 760	
lbs.	S	9090	9540	9880	10420	10840	11350	11670	12080	12350				lbs.	S	6175	
	D	16540	17360	18160	18960	19720	20820	21240	21980	22700					D	5675	
kg.	S	4120	4320	4480	4720	4920	5150	5300	5480	5600				kg.	S	2800	
	D	7480	7880	8240	8600	8960	9440	9640	9960	10300					D	2575	

305/75R24.5 LRH

LOAD PER AXLE														MAX LOAD PER TIRE*		
psi kPa		80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	130 900	135 930	psi kPa	115 (D) 790	123 (S) 850
lbs.	S	10715	11290	11860	12430	13000	13575	14155	14735	15315	15660			lbs.	S	7830
	D	20885	21930	22975	24020	25065	26110	27155	27780						D	6954
kg.	S	4860	5121	5380	5638	5897	6158	6421	6684	6947	7100			kg.	S	3550
	D	9473	9947	10421	10895	11369	11843	12318	12600						D	3150

305/75R24.5 LRH

LOAD PER AXLE													MAX LOAD PER TIRE *				
psi kPa		65 450	70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	psi kPa		115 790	
lbs.	S	9920	10530	11120	11710	12300	12870	13440	14000	14560	15120	15660		lbs.	S	7830	
	D	17580	18660	19720	20760	21800	22820	23820	24820	25820	26800	27760			D	6940	
kg.	S	4520	4760	5080	5320	5620	5840	6140	6380	6600	6880	7100		kg.	S	3550	
	D	8040	8440	9000	9440	9960	10360	10920	11320	11680	12200	12600			D	3150	

305/75R24.5 LRJ

LOAD PER AXLE													MAX LOAD PER TIRE *				
psi kPa		70 480	75 520	80 550	85 590	90 620	95 660	100 690	105 720	110 760	115 790	120 830	125 860	psi kPa		120 830	
lbs.	S	10750	11360	11960	12550	13140	13720	14300	14860	15420	15980	16540		lbs.	S	8270	
	D	18600	19660	20700	21740	22760	23760	24760	25740	26720	27680	28640			D	7160	
kg.	S	4840	5160	5400	5700	5940	6240	6460	6700	6980	7200	7500		kg.	S	3750	
	D	8400	8960	9360	9880	10280	10840	11200	11600	12120	12480	13000			D	3250	

