

2014 TIRE CHARTS

08/01/2013

SRW

TIRE SIZE	SIDE WALL	TREAD TYPE	SALES CODE	VEHICLE FAMILY	NAME	SUPPLIER	OVERALL DIAMETER	REVS PER MILE	STATIC LOAD-LB AT	MAX TIRE LOAD-LB AT	PSI MAX INFLATION PRESSURE
P265/70R17	OWL	A/S	TTY	DS	WRANGLER SRA	GOODYEAR	31.89	657	14.38	2,535	44
P265/70R17	BSW	A/S	TTM	DS	WRANGLER SRA	GOODYEAR	31.89	657	14.38	2,535	44
P265/70R17	BSW	O/O	TTS	DS	WRANGLER HP	GOODYEAR	31.47	670	14.07	2,535	44
LT265/70R17E	OWL	O/O	TXN	DS	WRANGLER SA	GOODYEAR	31.45	666	14.13	3,195	80
P275/60R20	BSW	O/O	TTN	DS	WRANGLER SRA	GOODYEAR	33.05	636	15.04	2,601	44
P275/60R20	OWL	O/O	TUB	DS	WRANGLER SRA	GOODYEAR	33.05	635	15.04	2,601	44
P275/60R20	OWL	O/O	TW6	DS	WRANGLER SA	GOODYEAR	32.96	640	14.89	2,601	44
285/45R22XL	BSW	A/S	TY4	DS	FORTERA SL	GOODYEAR	32.08	659	14.28	2,601	50
P235/85R17	VBS	SPARE	TBS	DS	RADIAL SPARE	GOODYEAR	32.4	640	14.41	2,535	44
LT245/70R17E	BSW	A/S	TWD + TZF	DJ	TRANSFORCE HT	FIRESTONE	30.55	678	14.33	3,000	80
LT285/70R17D	BSW	A/T	TW2	DJ	WRANGLER DURATRAC	GOODYEAR	32.8	632	15.31	3,195	65
LT265/70R18E	BSW	O/O	TDP	DJ / D2	LTX AT2	MICHELIN	32.8	642	15.26	3,525	80
LT275/70R18E	BSW	A/S	TCN	DJ / D2	TRANSFORCE HT	FIRESTONE	33.3	630	15.20	3,640	80
LT275/70R18E	OWL	A/S	TCP	DJ / D2	TRANSFORCE HT	FIRESTONE	33.3	630	15.24	3,640	80
LT285/60R20E	OWL	O/O	TEA	DJ / D2	TRANSFORCE AT	FIRESTONE	33.4	626	15.44	3,640	80

DRW

LT235/80R17E	BSW	A/S	TPY	2/DD 3,8 DRV	AMERITRAC	General	31.81	649	14.79	3,085	80
LT235/80R17E	OWL	O/O	TP9	2/DD 3,8 DRV	AMERITRAC TR	General	31.85	649	14.82	3,085	80
225/70R19.5 G	BSW	AP	TUV	DP 4,5,9,0	HSR	Continental	32.03	647	14.96	3970/3750	110
225/70R19.5 G	BSW	TR	TUZ	DP 4,5,9,0	HDR	Continental	32.14	647	15.00	3970/3750	110

A/S = Season
 O/O = On / Off Road
 P = Performance
 T = Touring
 AP = All Position / Steer
 TR = Traction / Drive
 AT = All Terrain



2014 TIRE CHARTS

08/01/2013

Passenger Car-Type Tubeless Tires

Size and Load Range (Ply Equivalent)	Maximum Capacity per Axle (lb)	Recommended Pressure Front/Rear (psi)	Static Load Radius (in)	Section Width (in)	Overall Diameter (in)	Revs/ Mile
Radial Tubeless						
P265/70R17 A/S	4,608	35	14.28	10.60	31.90	657
P265/70R17 On/Off	4,608	35	14.20	10.04	31.47	670
P275/60R20	4,368	35	14.92	11.20	33.05	635

Truck-Type Tubeless Tires

Size and Load Range (Ply Equivalent)	Maximum Capacity (lb) Single	Maximum Pressure (psi) Single	Static Loaded Radius (in)	Section Width (in)	Overall Diameter (in)	Revs/ Mile
LT245/70R17-E A/S	3,000	80	14.31	9.52	30.55	678
LT265/70R17-E A/S	3,195	80	14.65	10.35	31.45	666
LT265/70R17-D Q/O	3,195	65	15.33	11.06	32.80	632
LT235/80R17-E A/S	3,085	80	14.79	9.37	31.81	649
LT235/80R17-E Q/O	3,085	80	14.82	9.37	31.85	649
LT265/70R18-E	3,525	80	15.53	10.71	32.76	642
LT275/70R18-E	3,640	80	15.61	10.82	33.57	615
LT285/60R20-E	3,640	80	15.83	11.42	33.43	626

Light Truck-Type Tires -- Single Use

Size and Load Range	Maximum Capacity (lb)	Tire Load Limits at Various Cold Inflation Pressures -- Per Tire					
		35	45	55	65	75	80
LT245/70R17-E	3,000	1,890	2,010	2,315	2,800	2,875	3,000
LT265/70R17-E	3,195	1,890	2,255	2,595	2,910	3,100	3,195
LT265/70R17-D	3,195	2,105	2,510	2,900	3,195	-	-
LT235/80R17-E	3,085	1,725	2,055	2,370	2,880	2,940	3,085
LT265/70R18-E	3,525	1,960	2,340	2,690	3,085	3,345	3,525
LT275/70R18-E	3,640	2,070	2,470	2,840	3,195	3,530	3,640
LT285/60R20-E	3,640	2,020	2,410	2,775	3,085	3,445	3,640

Light Truck-Type Tires -- Dual Use

Size and Load Range	Tire Load Limits at Various Cold Inflation Pressures -- Per Tire					
	35	45	55	65	75	80
LT235/80R17-E	1,870	1,870	2,155	2,470	2,875	2,835

Medium Duty Truck-Type Tires -- Single Use

Size and Load Range	Maximum Capacity (lb)	Tire Load Limits at Various Cold Inflation Pressures -- Per Tire					
		80	85	90	95	100	110
225/70R19.5 G	3,970	3,195	3,315	3,450	3,540	3,715	3,845

Medium Duty Truck-Type Tires -- Dual Use

Size and Load Range	Tire Load Limits at Various Cold Inflation Pressures -- Per Tire					
	80	85	90	95	100	110
225/70R19.5 G	3,000	3,115	3,245	3,415	3,490	3,615

